

DuPont™ Vertrel® XF

SPECIALTY FLUID

Technical Information

Introduction

DuPont™ Vertrel® XF is a proprietary hydrofluorocarbon fluid with zero ozone-depletion and a low global warming potential ideally suited for use in vapor degreasing equipment for cleaning, rinsing, and drying. It can replace current hydrochlorofluorocarbon (HCFC) and perfluorocarbon (PFC) fluids in most applications.

DuPont™ Vertrel® XF is HFC 43-10mee or 2,3-dihydrodecafluoropentane; empirical formula $C_5H_2F_{10}$. It is a clear, colorless liquid with the properties shown in **Tables 1–2**.

Unique physical properties include a high density, low viscosity, and low surface tension. This combined with nonflammability, chemical and thermal stability, low toxicity, and ease of recovery by distillation make DuPont™ Vertrel® XF ideal for a broad range of applications. Solvency is selective, but can be enhanced by use of appropriate azeotropes and blends with alcohols, hydrocarbons, esters, etc. (see **Table 3**).

Typical Applications

- Cleaning and rinsing agent
- Drying fluid
- Particulate remover
- Fluorocarbon lubricant carrier
- Solvent and dispersion media
- Heat transfer media
- Dielectric fluid
- Replacement for many HCFC, PFC, and CFC-113 applications

DuPont™ Vertrel® XF is ideally suited for cleaning fine particulate matter (submicron range) from metal and nonmetal parts. Removal of particle contamination requires a solvent that can minimize the thickness of the laminar boundary layer where particles are bonded to the substrate. If the boundary layer thickness is less than the particle diameter, momentum from the flowing solvent can efficiently dislodge the particles and carry them away. DuPont™ Vertrel® XF, with its lower viscosity

and higher density, results in a thinner boundary layer, which enhances cleaning. Common aqueous cleaning fluids, mixtures of water and detergent, have higher viscosities and lower densities compared to DuPont™ Vertrel® XF, making these fluids less efficient.

The electronic attraction between particle and surface can be overcome further by increasing the polarity of the fluid through the addition of small amounts of alcohols. DuPont offers a series of proprietary azeotrope and blend compositions which exploit this property (see **Table 3**).

Table 1
Physical Properties

Property ^a	DuPont™ Vertrel® XF
Molecular Weight	252
Boiling Point, °C (°F)	55 (130)
Surface Tension, N/m (dyn/cm)	0.0141 (14.1)
Liquid Density, kg/liter (lb/gal)	1.58 (13.2)
Freezing Point, °C (°F)	–80 (–112)
Solubility in Water, ppm	140
Solubility of Water, ppm	490
Critical Temperature, °C (°F)	181 (357)
Critical Pressure, kPa (atm) (psia)	2288 (22.6) (331.9)
Critical Volume, liter/mol (cc/mol)	0.433 (433)
Heat of Vaporization (at boiling point), cal/g (kJ/kg)	31.0 (129.7)
Specific Heat at 20°C, kJ/kg·°C	1.13
Vapor Pressure, kPa (atm) (psia)	30.1 (0.297) (4.37)
Viscosity, cPs	0.67

^a At 25°C (77°F) except where indicated.

^b Pensky-Martens Closed Cup Tester (ASTM D 93)

^c Tag Open Cup Tester (ASTM D 1310)



The miracles of science™

Another common cleaning technique is the addition of ultrasonics to the solvent. High frequency, ultrasonic waves produce tiny bubbles which form and collapse (cavitate) as the wave passes. Cavitation energy increases with decreasing viscosity, another advantage of DuPont™ Vertrel® XF, improving its ability to mechanically dislodge particle contamination.

Vapor Degreasing Process

Use of modern vapor containment technology is recommended for both batch and in-line equipment. These systems have higher freeboard and a secondary set of low-temperature (–29°C [–20°F]) condenser coils to greatly reduce vapor losses from boiling solvent degreasing, defluxing, rinsing, and drying equipment.

Neat DuPont™ Vertrel® XF can be used for rinsing, drying, and some cleaning applications, but use with other components, such as azeotropes or simple blends, can provide improved solvency and soil removal. DuPont™ Vertrel® XF forms azeotropes or constant boiling mixtures with many similar boiling range components. Five nonflammable proprietary azeotrope compositions have been developed that are useful for general and precision cleaning and defluxing. See specific product bulletins for details.

Table 2
Density and Vapor Pressure Change with Temperature

Temperature, °C (°F)	Density, (kg/ltr)	Vapor Pressure, atm
–20 (–4)	1.70	0.021
–10 (14)	1.68	0.047
0 (32)	1.66	0.082
10 (50)	1.62	0.143
20 (68)	1.60	0.232
30 (86)	1.57	0.374
40 (104)	1.55	0.571
50 (122)	1.51	0.843
60 (140)	1.49	1.212
70 (158)	1.46	1.695
80 (176)	1.43	2.306
90 (194)	1.40	3.083
100 (212)	1.38	4.042
110 (230)	1.34	5.211
120 (248)	1.32	6.621
130 (266)	1.30	8.301

Table 3
Azeotropes of DuPont™ Vertrel® XF

Product	DuPont™ Vertrel® XF With	Boiling Point, °C (°F)
DuPont™ Vertrel® XM	Methanol	46 (115)
DuPont™ Vertrel® XE	Ethanol	52 (126)
DuPont™ Vertrel® XP	Isopropanol	52 (126)
DuPont™ Vertrel® MCA	Trans-1,2-Dichloroethylene	39 (102)
SMT	Trans-1,2-Dichloroethylene and Methanol	37 (99)

Solvency

Unlike the PFCs, DuPont™ Vertrel® XF is completely miscible with most esters, ketones, ethers, ether-alcohols, and the lower alcohols, such as methanol, ethanol, and isopropanol. The lower hydrocarbons, such as hexane and heptane, are also soluble. Neat DuPont™ Vertrel® XF has limited solvency for many higher molecular weight materials, such as hydrocarbon oils, silicone oils, waxes, and greases; here combinations with the many readily miscible esters, alcohols, and lower hydrocarbons can enhance solubility and cleaning efficiency. Like CFC-113 and the PFCs, DuPont™ Vertrel® XF has high solubility for Krytox® and “Fomblin” fluorocarbon lubricants and can be used either as an application carrier fluid or to remove them.

Plastic and Elastomer Compatibility

A large variety of plastics and elastomers can be safely exposed to DuPont™ Vertrel® XF. **Tables 4** and **5** summarize test results on short-term exposures of unstressed plastics and elastomers which simulate a typical cleaning cycle.

Long-term compatibility data simulating exposure of vapor degreaser construction materials is available from DuPont upon request.

Elastomer swelling and shrinking will, in most cases, revert to within a few percent of original size after air drying. Swell, shrinkage, and extractables are strongly affected by the compounding agents, plasticizers, and curing used in the manufacture of plastics and elastomers. Therefore, prior in-use testing is particularly important.

Table 4
Plastic Compatibility
Immersion: 15 Minutes at Room Temperature

Compatible	
Polyethylene	ABS
Polypropylene	Acetal
Polystyrene	Epoxy
Polyester, PET, PBT	Ionomer
Polyphenylene Oxide, PPO	Liquid Crystal Polymer
Polyimide, PI, PEI, PAI	Phenolic
Polyetherketone, PEK	PVC, CPVC
Polyaryletherketone, PEEK	PTFE, ETFE
Polysulfone	
Polyarylsulfone	
Polyphenylene Sulfide, PPS	
Incompatible ^a	
Acrylic	Cellulosic

^a Material composition varies depending upon compounding agents, plasticizers, processing, etc. Specific materials should be tested for compatibility with solvent.

Table 5
Elastomer Compatibility
Immersion: 15 Minutes at Room Temperature

Compatible	
Buna N, NBR, Nitrile	Buna S, SBR, GRS
Butyl Rubber, IIR	Chlorosulfonated PE
EPM, EPDM, Nordel®	Polysulfide
Natural Rubber, Isoprene	Neoprene
Urethane	Viton® B
	Silicone
Incompatible ^a	
None Tested	

^a Material composition varies depending upon compounding agents, plasticizers, processing, etc. Specific materials should be tested for compatibility with solvent.

Metals and Other Compatibility

DuPont™ Vertrel® XF is fully compatible with the metals listed below after exposure for two weeks at 100°C (212°F) in sealed tubes with and without water contact.

- Zinc*
- Aluminum
- Stainless Steel
- Copper*
- Brass*

DuPont™ Vertrel® XF is not compatible with strong bases; therefore, contact with highly basic process materials is not recommended.

*Slight discoloration with water present

Exposure Limits

Data from acute toxicity studies has demonstrated that DuPont™ Vertrel® XF has low toxicity. DuPont™ Vertrel® XF is a slight skin and eye irritant and has low acute inhalation toxicity. **Table 6** shows the applicable exposure limits for DuPont™ Vertrel® XF.

Table 6
Exposure Limits

Component	Limit, ppm	Type
DuPont™ Vertrel® XFAEL ^a	200 400	8- and 12-hr TWA Ceiling ^b

^a AEL (Acceptable Exposure Limit) is an airborne inhalation exposure limit established by DuPont that specifies time-weighted average concentrations to which nearly all workers may be repeatedly exposed without adverse effects.

^b A ceiling limit is the concentration that should not be exceeded during any part of the working day. The ceiling limit for individual components applies to a blend product as well.

Safety/Flammability

DuPont™ Vertrel® XF is nonflammable and does not become flammable during boiling or evaporation. It exhibits no closed or open cup flash point, and is not classified as a flammable liquid by NFPA or DOT. It is thermally stable to 300°C (572°F) and does not oxidize or degrade during storage.

Recovery

DuPont™ Vertrel® XF is a pure component material, and is easily recoverable by off-line and in-line distillation equipment such as a vapor degreaser or still. The presence of soil, however, may alter the characteristics of the material during the recovery operation. Recovery should be closely monitored to ensure operating levels are maintained. Users should test the spent DuPont™ Vertrel® XF to ensure proper classification for waste disposal.

Storage/Handling

DuPont™ Vertrel® XF is thermally stable and does not oxidize or degrade during storage. Store in a clean, dry area. Protect from freezing temperatures. Do not allow stored product to exceed 52°C (125°F) to prevent leakage or potential rupture of container from pressure and expansion.

Consideration should be given to retrofit of existing, or purchase of new, vapor degreasing equipment to provide vapor containment technology that enables safe and economical use of DuPont™ Vertrel® XF.

Drum pumps are recommended to dispense DuPont™ Vertrel® XF from its container. Refer to the Material Safety Data Sheet for specific handling precautions and instructions.

Environmental Legislation

DuPont™ Vertrel® XF has zero ozone-depletion potential and a low global warming potential (**Table 7**). DuPont™ Vertrel® XF and its azeotropes and blends are used as alternatives to CFC-113, methylchloroform, hydrochlorofluorocarbons (HCFCs), and perfluorocarbons (PFCs) in many critical cleaning, drying, carrier fluid, and other high-value specialty uses where reliability is paramount.

DuPont™ Vertrel® XF is accepted by the U.S. Environmental Protection Agency (EPA) under the Significant New Alternatives Policy (SNAP) program as a substitute for ozone-depleting substances. HFC 43-10mee or decafluoropentane is exempt from classification as a volatile organic compound (VOC) by the EPA. DuPont™ Vertrel® XF is also VOC compliant under the California South Coast Air Quality Management District (SCAQMD) regulations, which require VOC content less than 50 g/L of solvent.

DuPont™ Vertrel® XF is listed in the TSCA inventory. It is subject to the Significant New Use Rule (SNUR) and should be used only in the indicated applications. See MSDS Regulatory Section.

DuPont™ Vertrel® XF is not a hazardous air pollutant (HAP), and therefore not subject to NESHAP regulation. Spent DuPont™ Vertrel® XF is not a RCRA characteristic or listed waste. However, addition of contaminants could change that status. DuPont™ Vertrel® XF is not included in the SARA Title III Section 313 list of toxic chemicals, and is not subject to SARA Title III (EPCRA) reporting requirements.

Packaging and Availability

DuPont™ Vertrel® XF is commercially available in 55-gal (208-L) drums with a net weight of 660 lb (299 kg) and in 5-gal (20-L) pails with a net weight of 60 lb (27 kg). One-gallon and smaller samples in glass containers are available on request. Customers are encouraged to secure samples now for compatibility and performance testing.

Specifications

Composition and specifications are shown in **Table 8**. DuPont™ Vertrel® XF is listed in the TSCA Inventory.

Table 8
DuPont™ Vertrel® XF Specifications

Fluoropentanes, wt%	99.9 min.
Nonvolatile Residue, ppm wt	2.0 max.
Moisture, ppm wt	50 max.
Acidity, mg KOH/g	0.01 max.
Appearance	Clear, Colorless

Table 7
Environmental Properties

Property	DuPont™ Vertrel® XF
Formula	C ₅ H ₂ F ₁₀
Class	Hydrofluorocarbon (HFC)
Atmospheric Lifetime, yr	17.1
Ozone-Depletion Potential (ODP)	0
Global Warming* Potential (GWP/100 yr ITH)	1300
Volatile Organic Compounds (VOC, g/L)	Exempt

* IPCC Second Assessment Report (1995)

If you are interested in purchasing or finding out more about DuPont™ Vertrel® please use the list below to contact the DuPont office closest to you.

North America

DuPont Fluorochemicals
Customer Service Center
Chestnut Run Plaza 702
Wilmington, DE 19880-0702
Ph: 800-969-4758 (U.S. only)
Ph: 1-302-774-1160 (Outside U.S.)

Europe, Middle East, Africa

DuPont de Nemours Intl., S.A.
2, Chemin du Pavillon
CH-1218 Le Grand-Saconnex/GE
Switzerland
Ph: 41 22 717 5296
Fax: 41 22 717 6169

Asia Pacific

DuPont-Mitsui Fluorochemicals Co. Ltd.
Chiyoda Honsha Building
1-5-18 Sarugaku-cho
Chiyoda-Ku Tokyo 101
Japan
Ph: 03 5281 5850 (Japan only)
Ph: 1-302-774-1160 (All others)

Copyright © 2008 DuPont or its affiliates. All rights reserved. The DuPont Oval Logo, DuPont™, The miracles of science™, and Vertrel®, are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates.

NO PART OF THIS MATERIAL MAY BE REPRODUCED, STORED IN A RETRIEVAL SYSTEM OR TRANSMITTED IN ANY FORM OR BY ANY MEANS ELECTRONIC, MECHANICAL, PHOTOCOPYING, RECORDING OR OTHERWISE WITHOUT THE PRIOR WRITTEN PERMISSION OF DUPONT.

The information set forth herein is furnished free of charge and is based on technical data that DuPont believes to be reliable. It is intended for use by persons having technical skill, at their own discretion and risk. The handling precaution information contained herein is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards. Because conditions of product use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any material, evaluation of any compound under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate under or a recommendation to infringe any patents.

CAUTION: Do not use in medical applications involving permanent implantation in the human body or contact with internal body fluids or tissues. For other medical applications, see "DuPont Medical Caution Statement," H-50102.

